

The Cathode preparation and transport system for the Gatling Gun

Omer Rahman

Collider Accelerator Department, Brookhaven National Lab
Department of Physics and Astronomy, Stony Brook University
orahman@bnl.gov

September 11, 2013

Overview

- Motivation and key objectives
- Cathode preparation chamber-step by step design
- Heat cleaning and Activation
- The Cathode storage and transport system to the Gun
- Conclusion and future plan

Motivation

The proposed eRHIC project requires an electron source with the following main parameters :

- High Average Current: 50 mA
- High polarization: $P > 80\%$

50 mA from one cathode for one week = 15,300 C

State of the art charge lifetime = 1000 C.

50 mA distributed over 20 cathodes = 2.5mA per cathode for one week = 765 C Charge lifetime!

The Funnelling Principle

Our main objectives are:

- To investigate the status of one cathode i.e. change in QE, lifetime etc., in the vicinity of another operating cathode.
- To funnel multiple bunches to one common axis using a rotating magnetic field.

For Phase 1 of the experiment, we aim to combine two bunches from two bulk GaAs photocathodes.

The Gatling Gun





Figure: The Gatling Gun side view, details at E. Wang's talk

Grand Central and The Tree



- Image courtesy: John Skaritka

GaAs: Established and widely used source of polarized electrons

Bulk GaAs: Maximum 50% polarization

Superlattice GaAs: More than 80% polarization

Highly sensitive to vacuum!

Requires "Activation" before photoemission.

Step by step construction of the tree




Figure: Front view of the actual tree

Step by step construction of the tree




Figure: View through the top window

Step by step construction of the tree




Figure: Lower Cross includes Turbo line and NEG

Step by step construction of the tree




Figure: Second Cross includes NEG, Filament assembly, window and ion pump

Step by step construction of the tree






Figure: Third Cross includes Anode, Cs Source, Window, Oxygen valve and Gauge

Step by step construction of the tree

So all together



Pressure





Figure: Sample Pressure Vs Time graph for the tree

Heat cleaning of the sample

Conventional heat cleaning using a readily available Tungsten filament from a 250W light bulb..... that costs \$1.27.



However, the glass has to be machined off very carefully.

Heat cleaning of the sample





Figure: Schematic diagram of heat cleaning

Activation

- Set up the necessary instrumentation i.e. laser, electrometer, battery etc.
- Evaporate Cs from by flowing current through the source.
- After 350 Seconds, the first real signal is seen.
- After 500 seconds, Cs peak and current starts to fall
- Open Oxygen valve as current is falling, it starts to rise again
- Adjust leak valve to obtain maximum rate of increase
- Close leak valve and turn off Cs as current saturates

Typical Activation Curve



The Cathode Storage AKA Grand Central




Figure: Actual Grand Central on the left, cross sectional view on the right

Transport of cathode from Grand Central to Tree 1





Figure: Cathodes are loaded in the load lock chamber which will be baked before the valve is open to Grand Central

Transport of cathode from Grand Central to Tree 2





Figure: Once the load-lock chamber is in XHV, valve is opened and Cathodes are inside Grand Central. Using of a fork lift to bring the cathodes up to the tree

Transport of activated cathode from Grand Central to the Gun Shroud 1





Figure: Activated cathodes are put on the train using the fork lift which is moved to the Gun Shroud

Side view of the Grand Central with the manipulators






Figure: Side view of the Grand Central with the two manipulators to transport the Cathodes

Transport of activated cathodes from Grand Central to Gun Shroud 2



Conclusion

- Cathode chamber was assembled
- XHV achieved on a consistent basis
- Bulk GaAs activated with 8% QE
- Grand Central and Cathode transport systems are being built and are scheduled to be tested by the end of this year

Future Plan

- Optimize the design of the chamber
- Combine two beams to test funelling using bulk GaAs for low current in early 2014
- If successful, eventually use Superlattice GaAs to obtain highly polarized beam

Acknowledgment

BNL Gatling Gun Group: Ilan Ben-Zvi, David Gassner, Alexander Pikin, Triveni Rao, Eric Riehn, Brian Sheehy, John Skaritka, Erdong Wang and Qiong Wu.

Thank you For you attention!

Side view of the Gun showing the transport line

